PLATE 4 OF 10

EXPLANATION

ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred. Isopach interval 1 foot.

STRUCTURE CONTOURS - Drawn on top of coal bed. Solid where vertical accuracy within 40 feet; long dashed where vertical accuracy possibly not within 40 feet; short dashed where projected above ground sur-face. Contour interval 200 feet (61 m). Datum is mean sea level.

5.6/0.3

DRILL HOLE - Showing altitude of top of coal bed and total coal thickness/total rock thickness.

POINT OF MEASUREMENT - Showing altitude of top of coal bed, and thickness of coal, in feet. Includes all points of measurement other than drill holes.


MK - Main Kemmerer SV[1] - Spring Valley [1]

COAL BED SYMBOLS AND NAMES - Coal beds identified by bracketed numbers are not formally named, but are numbered for identification purposes in this quadrangle

TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Short dashed where inferred by present authors.

SUBSURFACE COAL MINE - Showing name of mine. Dashed where approximately located.

To convert feet to meters, multiply feet by 0.3048.



COAL RESOURCE OCCURRENCE MAP OF THE NORTHEAST QUARTER OF THE KEMMERER 15-MINUTE QUADRANGLE, LINCOLN COUNTY, WYOMING

> BY DAMES & MOORE 1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.